

402.1683

INTERLOCKED SOCKET
 16A 2P+E 6h 200-250V 60Hz 50Hz
 130X260MM Screw terminals With
 mechanical interlock



EN 60309-4 (2007)
 EN 60309-1 (1999)
 EN 60309-2 (1999)
 EN 60309-1/A1 (2007)
 EN 60309-2/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	ADVANCE GRP Series
Synthetical description	INTERLOCKED SOCKET

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Colour	BLUE
Material	GRP Glass Reinforced Polyester
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK10
Contact material	CuZn (brass)
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Padlock	ø5mm

■ DIMENSIONAL CHARACTERISTICS

Flange	130X260MM
--------	-----------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER