Ledinaire Recessed Downlight

DN070B LED12/830 12W 220-240V D150 RD EU

The new LEDINAIRE recessed downlight offers excellent light quality, high efficacy with visual comfort. Available in two sizes with two lumen options & two CCT options to suit different applications. This is a real professional choice for everyday lighting installations

Product data

General information	
Light source colour	830 warm white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Optic type	60 [Beam angle 60°]
Luminaire light beam spread	60°
Connection	Connection unit 2-pole
Cable	Cord 0.25 m with push-in connector
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	Yes
Warranty period	3 years
Constant light output	No
Number of products on MCB (16 A type B)	245
EU RoHS compliant	Yes
Unified glare rating CEN	19

Operating and electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Inrush current	7.85 A
Inrush time	0.18 ms
Power factor (min.)	0.9

Controls and dimming	
Dimmable	No

Mechanical and housing	
Housing material	Metal–Plastic
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Matt
Overall length	170 mm
Overall width	170 mm
Overall height	82 mm

Ledinaire Recessed Downlight

Overall diameter	170 mm
Colour	Black
Dimensions (height x width x depth)	82 x 170 x 170 mm

Approval and application

Ingress protection code	IP20/54 [Finger-protected; dust accumulation-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1200 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	96.00 lm/W
Init. Corr. Colour Temperature	3000 K
Init. Colour rendering index	80
Initial chromaticity	(0.4300, 0.4081) 5SDCM
Initial input power	12 W
Power consumption tolerance	+/-10%

Over time performance (IEC compliant)

Driver failure rate at 5,000 hours	0.6 %
Lumen maintenance at median useful life* 50,000 h	L65

Application conditions

Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

Product data

Full product code	871951435398500
Order product name	DN070B LED12/830 12W 220-240V D150 RD EU
EAN/UPC – product	8719514353985
Order code	35398500
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	929003165332
Net Weight (Piece)	0.440 kg

F IK03

Dimensional drawing



Cut-out hole diameter - Ø150mm

DN070B LED12/830 12W 220-240V D150 RD EU

Photometric data



Downlight DN070B 830 12W D150 RD-EU-LDD



Downlight DN070B 830 12W D150 RD-EU-GUL

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.