



Essential SmartBright G5 LED Floodlight

BVP150 LED150/CW PSU 150W SWB G3 CN

Essential SmartBright G5 LED Floodlight, 15000 lm, 150 W, 865 cool daylight, 110°, Safety class I, Mounting bracket

The Essential SmartBright G5 LED Floodlight is the new successor with robust die-cast aluminum housing suitable for general outdoor application. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

Product data

General Information		Optic type	Wide beam
Number of gear units	1 unit	Luminaire light beam spread	110°
Gear	-	Effective projected area	0.09 m²
Driver included	Yes	Operating and Electrical	
Light source engine type	LED	Input Voltage	220 to 240 V
Value ladder	Value	Line Frequency	50 or 60 Hz
Warranty period	2 years	Inrush current	10 A
Light Technical		Inrush time	0.03 ms
Luminous Flux	15,000 lm	Power Consumption	150 W
Correlated Color Temperature (Nom)	6500 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	100 lm/W	Connection	Flying leads/wires
Color rendering index (CRI)	80	Cable	Cable 0.7 m without plug
Number of light sources	1	Number of products on MCB of 16 A type B	15
Beam angle of light source	110 degree(s)	Suitable for random switching	No
Light source color	865 cool daylight		

Essential SmartBright G5 LED Floodlight

Protection class IEC	Safety class I
----------------------	----------------

Controls and Dimming

Dimmable	No
Control interface	-
Maximum dim level	Not applicable

Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Glass
Housing Color	Black
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	387 mm
Overall width	315 mm
Overall height	39 mm
Dimensions (Height x Width x Depth)	39 x 315 x 387 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Optical cover type	Tempered glass
Net Weight (Piece)	2.400 kg

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	No
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	-40 to +50 °C


Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.31, 0.34) SDCM≤6
Power consumption tolerance	+/-10%

Product Data

Order product name	BVP150 LED150/CW PSU 150W SWB G3 CN
Full product name	BVP150 LED150/CW PSU 150W SWB G3 CN
Full product code	692382867353699
Order code	911401837186
Material Nr. (12NC)	911401837186
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828673536
Numerator - Packs per outer box	6
EAN/UPC - Case	6923828673772

Dimensional drawing



Essential SmartBright G5 LED Floodlight

