

80-125W

- 非隔离式
 - 效率高达93%
 - 细长型金属外壳
 - 输出电流纹波: ± 3%
 - 具有16种电流选择 (通过DIP开关)
- Non-Isolated
 - Efficiency up to 93%
 - Linear housing
 - Typical ripple current: ± 3%
 - Selectable constant current output (16 in 1/Via DIPswitch)



产品型号 Model No.	输入电压 Input Voltage	功率因数 Power Factor	输出功率 Output Power	输出电流 Output Current	输出电压 Output Voltage	尺寸 Dimension
CDZ-LED-TH80-350AN-DD	220-240V	0.98	64W max.	200mA	70-320V	280*30*21mm (A1)
			67W max.	210mA	70-320V	
			70W max.	220mA	70-320V	
			73W max.	230mA	70-320V	
			76W max.	240mA	70-320V	
			75W max.	250mA	70-300V	
			78W max.	260mA	70-300V	
			81W max.	270mA	70-300V	
			78W max.	280mA	70-280V	
			81W max.	290mA	70-280V	
			78W max.	300mA	70-260V	
			80W max.	310mA	70-260V	
			77W max.	320mA	70-240V	
			79W max.	330mA	70-240V	
			81W max.	340mA	70-240V	
			84W max.	350mA	70-240V	
CDZ-LED-TH80-700AN-DD	220-240V	0.98	78W max.	325mA	50-240V	280*30*21mm (A1)
			84W max.	350mA	50-240V	
			83W max.	375mA	50-220V	
			80W max.	400mA	50-200V	
			81W max.	425mA	50-190V	
			81W max.	450mA	50-180V	
			81W max.	475mA	50-170V	
			80W max.	500mA	50-160V	
			79W max.	525mA	50-150V	
			83W max.	550mA	50-150V	
			81W max.	575mA	50-140V	
			78W max.	600mA	50-130V	
			81W max.	625mA	50-130V	
			79W max.	650mA	50-120V	
			81W max.	675mA	50-120V	
			84W max.	700mA	50-120V	
CDZ-LED-TH125-1050AN-DD	220-240V	0.98	125W max.	500mA	120-250V	360*30*21mm (A2)
			120W max.	525mA	120-230V	
			121W max.	550mA	120-220V	
			120W max.	575mA	120-210V	
			120W max.	600mA	70-200V	
			125W max.	625mA	70-200V	
			123W max.	650mA	70-190V	
			121W max.	675mA	70-180V	
			119W max.	700mA	50-170V	
			120W max.	750mA	50-160V	
			120W max.	800mA	50-150V	
			119W max.	850mA	50-140V	
			117W max.	900mA	50-130V	
			123W max.	950mA	50-130V	
			120W max.	1000mA	50-120V	
			126W max.	1050mA	50-120V	

0-10V可调光

- 隔离式/SELV
 - 效率高达88%
 - 细长型金属外壳
 - 输出电流纹波: ± 3%
- Isolated/SELV
 - Efficiency up to 88%
 - Linear housing
 - Typical ripple current: ± 3%



产品型号 Model No.	输出功率 Output Power	输入电压 Input Voltage	输出电压 Output Voltage	输出电流 Output Current	认证 Product certification	效率 Efficiency	功率因数 Power Factor	尺寸 Dimension
CDZ-LED-75-1800A-DDF-SR	75.5W	220-240V	15-42V	1800mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	103*67*31mm
	65W	220-240V	15-42V	1550mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	56.5W	220-240V	15-42V	1350mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	52.5W	220-240V	15-42V	1250mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
CDZ-LED-50-1200A-DDF-SR	50.5W	220-240V	15-42V	1200mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	44W	220-240V	15-42V	1050mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	40W	220-240V	15-42V	950mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	35.5W	220-240V	15-42V	850mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
CDZ-LED-50-1050A-DDF-SR	50.5W	220-240V	20-48V	1050mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	44W	220-240V	20-48V	900mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	40W	220-240V	20-48V	800mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	35.5W	220-240V	20-48V	700mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
CDZ-LED-30-700A-DDF-SR	29.5W	220-240V	15-42V	700mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	25W	220-240V	15-42V	550mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	21W	220-240V	15-42V	400mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	
	19W	220-240V	15-42V	350mA	CE/CB/TUV/CCC/SAA/RCM/ENEC	90%	0.95	

产品性能

- 输入：额定电压220-240V，极限电压187-264V。
- 性能：1.高PF值，低谐波，无频闪，高效率。 2.满足ERP灯具认证要求。 3.防雷防护：2KV/4KV。
- 调光方式：0-10V调光
- 质保：质保五年。
- 使用领域：筒灯，面板灯，投光灯、格栅灯、轨道灯等LED灯具。

Feature

- Input: Rated voltage 220-240V, limit voltage 187-264V.
- IPerformance: 1. High PF value, low harmonic, no stroboscopic, high efficiency. 2. Meet the requirements of ERP lighting certification. 3.Lightning protection: 2KV/4KV.
- IDimming mode: 0-10V dimming
- IWarranty: Five years warranty.
- IField of use: downlights, panel lights, floodlights, grid lights, track lights and other LED lamps.