



Overview

Mounting	Recessed ceiling
Material	Aluminum, paint; Plastic mounting ring
Cut-out	200mm
Finishing	White
IP rating	54

Electrical

Power supply	220-240Vac
Gear	LED Driver
Dimming	Triac/ 1-10V/ DALI
Installation	Remote
Insulation class	III
Output voltage	36.4-39V
Current intensity	500mA
Driver lifespan	40,000Hrs
Certification	CE/ IP Report

Accessories

N/A

Lamp

Light source	LED																		
Power	18.5W																		
Nominal flux	3152.2Lm																		
Optical efficiency	81%																		
Fixture flux	2556.1Lm																		
Color temperature	4000K																		
SDCM	3																		
CRI	80																		
Beam angle	80°																		
Tilting angle	-																		
Rotating angle	-																		
LED lifespan	50,000Hrs L80B10																		
Photometric	<table border="1"> <thead> <tr> <th colspan="3">Beam angle 80° 4000K</th> </tr> </thead> <tbody> <tr> <td>1599</td> <td>1.678</td> <td>1.0</td> </tr> <tr> <td>400</td> <td>3.356</td> <td>2.0</td> </tr> <tr> <td>178</td> <td>5.034</td> <td>3.0</td> </tr> <tr> <td>100</td> <td>6.712</td> <td>4.0</td> </tr> <tr> <td>E (lx)</td> <td>D (m)</td> <td>H (m)</td> </tr> </tbody> </table>	Beam angle 80° 4000K			1599	1.678	1.0	400	3.356	2.0	178	5.034	3.0	100	6.712	4.0	E (lx)	D (m)	H (m)
Beam angle 80° 4000K																			
1599	1.678	1.0																	
400	3.356	2.0																	
178	5.034	3.0																	
100	6.712	4.0																	
E (lx)	D (m)	H (m)																	

Beam angle 80° 4000K		
1599	1.678	1.0
400	3.356	2.0
178	5.034	3.0
100	6.712	4.0
E (lx)	D (m)	H (m)



Dimension

