









防爆投光灯 EXPLOSION-PROOF FLOOD LIGHT



壁式 Wall type



吸顶式 Ceiling type



底座式 Base type

适用范围 The scope of application	适用于温度组别为T1-T4爆炸性气体场所1区、2区的环境中使用时，也适用于船舶、石油平台等室外远距离照明。Applied to the explosive gas place zone 1 zone 2 with the temperature group T1-T4, also suitable for remote illumination. in ships, oil platforms and etc.			
型号 Type	CFT2			
防爆标志 Explosion-proof mark	Ex de IIB T3 Gb			
额定电压 Rated voltage	AC110V 60Hz、AC220V 50/60Hz			
功率 Power	250W		400W	
光源 Illuminant	高压钠灯 High-pressure sodium lamp	金属卤化物灯 Metal halide lamp	高压钠灯 High-pressure sodium lamp	金属卤化物灯 Metal halide lamp
光通量 Luminous flux	26000lm	20500lm	47000lm	26000lm
功率因数 Power factor	≥0.85			
灯座 Lamp holder	E40			
调节方式 Adjustment mode	仰俯45° pitch 45			
防护等级 Protection class	IP56			
电缆外径 Cable outside diameter	Ø13~Ø14			
安装方式 Installation method	壁式 Wall type 吸顶式 Ceiling type 底座式 Base type			
环境温度 Ambient temperature	-20℃ ~ +45℃			
灯体材质 Lamp body material	铝 Aluminum			
灯罩材质 Lamp shade material	钢化玻璃 Toughened glass			
重量 Weight	24.5kg			