



Technical Hotline
+44 (0)1268 563720

Logic Plus™

WIRING DEVICES
WHITE

Socket Outlets

2P + E
FLUSH
16 AMP
(NON UK)



K4150WHI



K4152WHI

Three Pole Fan Isolator

FLUSH
10 AMP



K4857WHI



K4859WHI



K4858



K2000

Shaver Socket Outlet



K700WHI

Shaver/Toothbrush Supply Units



K701WHI



K706WHI

K4150WHI

1 GANG
16A 250V
SHUTTERED
(NON UK)

10

K4152WHI

2 GANG
16A 250V
SHUTTERED
(NON UK)

5

MOUNTING BOXES

FLUSH 35MM
1 GANG: 866ZIC
2 GANG: 886ZIC

SURFACE

1 GANG: K2031WHI
2 GANG: K2172WHI

These products are not suitable for installation in 25mm boxes.

DIMENSIONS

1 GANG: 86 x 86mm
2 GANG: 86 x 146mm

FIXING CENTRES

1 GANG: 60.3mm
2 GANG: 120.6mm
IEC 60884-1:2006

K4857WHI

WITH SWITCHLOCK
AND PADLOCK

1

K4859WHI

WITHOUT SWITCHLOCK

10

K4858

SWITCHLOCK
FOR FAN ISOLATOR

10

K2000

PADLOCK

1

MOUNTING BOXES

FLUSH
3995ZIC

SURFACE

K2160WHI

For local isolation of fans with or without timers for repair or routine maintenance.

DIMENSIONS

86 x 86mm

FIXING CENTRES

60.3mm

BS EN 60669-2-4

K700WHI

SHAVER SOCKET OUTLET
200-250 VOLTS 50/60HZ
FUSED
INCORPORATES A SELF-RESETTING
OVERLOAD DEVICE, LIMITING
CURRENT TO 20VA.

1

MOUNTING BOXES

FLUSH

861ZIC

SURFACE

K2140WHI

Must not be installed in a bathroom or shower room.

DIMENSIONS

86 x 86mm

FIXING CENTRES

60.3mm

BS 4573:1970

K701WHI

SHAVER/TOOTHBRUSH
SUPPLY UNIT
DUAL VOLTAGE
115/230V OUTPUT
(220/240V 50/60HZ INPUT)

1

K706WHI

SHAVER/TOOTHBRUSH
SUPPLY UNIT
DUAL VOLTAGE
115/230V OUTPUT
(120/130V 50/60HZ INPUT)
(NON UK)

1

MOUNTING BOXES

FLUSH

878ZIC

SURFACE

K2172WHI

This design incorporates a double wound isolating transformer rated 20VA at 230 or 115 volts it meets BS EN 61558 making it safe for use in bathrooms. Insertion of a shaver/toothbrush plug automatically switches on by energising the primary side of the isolating transformer – removal automatically switches off. The transformer is protected against overload by an automatic solid state overload device with automatic resetting.

DIMENSIONS

146 x 86mm

FIXING CENTRES

120.6mm

BS EN 61558-2-5:1998