



# LED 4W Clear Filament Bent Tip Candle - SES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament Candle is ideal for all chandeliers and wall lights.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

#### **Technical Specification**

Product Code	05026
Reference	
Guarantee	3 Years
EAN	5013588050263
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Сар	SES/E14
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	22mA
Energy Consumption (kWh/1000h)	4
Dimensions	
	445
Height (mm)	115
Diameter (mm)	35
Packaging Information	
Single Carton Height (mm)	135
Single Carton Width (mm)	40
Single Carton Depth (mm)	40
Single Carton Weight (kg)	0.04
Individual Volume	0.00022
Inner Box Qty	10
Inner Box Height (mm)	150
Inner Box Width (mm)	220
Inner Box Depth (mm)	90
Inner Box Weight (kg)	0.41
Outer Box Qty	100
Outer Box Height (mm)	310
Outer Box Width (mm)	480
	400







# LED 4W Satin Filament Bent Tip Candle - SES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament Candle is ideal for all chandeliers and wall lights.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

#### **Technical Specification**

Product Code	05027
Reference	
Guarantee	3 Years
EAN	5013588050270
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Сар	SES/E14
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	22mA
Energy Consumption (kWh/1000h)	4
Dimensions	
Height (mm)	115
Diameter (mm)	35
Packaging Information	
Single Carton Height (mm)	135
Single Carton Width (mm)	40
Single Carton Depth (mm)	40
Single Carton Weight (kg)	0.04
	0.01
Individual Volume	0.00022
Individual Volume	
	0.00022
Inner Box Qty	0.00022
Inner Box Qty Inner Box Height (mm)	0.00022 10 150
Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	0.00022 10 150 220
Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	0.00022 10 150 220 90
Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	0.00022 10 150 220 90 0.41
Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	0.00022     10     150     220     90     0.41     100







# LED 1W Clear Filament Chandelier - SES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament Candle is ideal for all chandeliers and wall lights.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

#### **Technical Specification**

Product Code	05028
Reference	
Guarantee	3 Years
EAN	5013588050287
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	1
Сар	SES/E14
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	100
Life Hours	15000
Beam Angle	300°
Energy Rating	G
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	11mA
Energy Consumption (kWh/1000h)	1
Dimensions	
Height (mm)	86
Diameter (mm)	22
Packaging Information	
Single Carton Height (mm)	30
Single Carton Height (mm) Single Carton Width (mm)	30 30
Single Carton Width (mm)	30
Single Carton Width (mm) Single Carton Depth (mm)	30 105
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	30   105   0.02
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume	30     105     0.02     0.00009
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	30     105     0.02     0.00009     20
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm)	30     105     0.02     0.00009     20     165
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	30     105     0.02     0.00009     20     165     130
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	30     105     0.02     0.00009     20     165     130     115
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	30     105     0.02     0.00009     20     165     130     115     0.53
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	30     105     0.02     0.00009     20     165     130     115     0.53     100
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	30     105     0.02     0.00009     20     165     130     115     0.53     100     675







# LED 1W Clear Filament Chandelier - MES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament Candle is ideal for all chandeliers and wall lights.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

#### **Technical Specification**

Product Code	05029
Reference	
Guarantee	3 Years
EAN	5013588050294
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	1
Сар	MES/E10
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	100
Life Hours	15000
Beam Angle	300°
Energy Rating	G
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	11mA
Energy Consumption (kWh/1000h)	1
Dimensions	
Height (mm)	83
Diameter (mm)	22
Packaging Information	
Single Carton Height (mm)	30
Single Carton Width (mm)	30
Single Carton Depth (mm)	105
Single Carton Weight (kg)	0.02
Individual Volume	0.00009
Inner Box Qty	20
Inner Box Height (mm)	165
Inner Box Width (mm)	130
Inner Box Depth (mm)	115
Inner Box Weight (kg)	0.53
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	185
Outer Box Depth (mm)	135
Outer Box Weight (kg)	3.05

