



# LED 4W Satin Dimmable Filament GLS - BC - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588052861
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Watts (W)         4           Cap         BC/B22           Colour Temp (K)         2700           Dimmable?         Yes           Lumens (Im)         450           Life Hours         15000           Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         Height (mm)         102           Diameter (mm)         60           Packaging Information         Single Carton Height (mm)         125           Single Carton Width (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Qty         10           Inner Box Height (mm)         140           Inner Box Depth (mm)         140           Inner Box Weight (kg)         0.65           Outer Box Oty         100	Volts (V)	240
Colour Temp (K)         2700           Dimmable?         Yes           Lumens (Im)         450           Life Hours         15000           Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         Height (mm)         102           Diameter (mm)         60           Packaging Information         Single Carton Height (mm)         125           Single Carton Width (mm)         65           Single Carton Depth (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Oty         10           Inner Box Height (mm)         140           Inner Box Weight (kg)         0.65	Watts (W)	4
Dimmable?         Yes           Lumens (Im)         450           Life Hours         15000           Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         Height (mm)         102           Diameter (mm)         60           Packaging Information         Single Carton Height (mm)         125           Single Carton Width (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Qty         10           Inner Box Height (mm)         140           Inner Box Width (mm)         340           Inner Box Weight (kg)         0.65	Сар	BC/B22
Lumens (Im)         450           Life Hours         15000           Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         Height (mm)         102           Diameter (mm)         60           Packaging Information         Single Carton Height (mm)         125           Single Carton Width (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Qty         10           Inner Box Height (mm)         140           Inner Box Width (mm)         340           Inner Box Depth (mm)         140           Inner Box Weight (kg)         0.65	Colour Temp (K)	2700
Life Hours         15000           Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         Height (mm)         102           Diameter (mm)         60           Packaging Information         Single Carton Height (mm)         125           Single Carton Width (mm)         65           Single Carton Depth (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Qty         10           Inner Box Height (mm)         140           Inner Box Width (mm)         340           Inner Box Depth (mm)         140           Inner Box Weight (kg)         0.65	Dimmable?	Yes
Beam Angle         300°           Energy Rating         E           CRI (ra)         85           Switching Cycles         8000           Frequency (Hz)         50/60           Energy Consumption (kWh/1000h)         4           Dimensions         102           Height (mm)         102           Diameter (mm)         60           Packaging Information         125           Single Carton Height (mm)         65           Single Carton Width (mm)         65           Single Carton Weight (kg)         0.05           Individual Volume         0.00053           Inner Box Qty         10           Inner Box Height (mm)         140           Inner Box Width (mm)         340           Inner Box Depth (mm)         140           Inner Box Weight (kg)         0.65	Lumens (lm)	450
Energy Rating E  CRI (ra) 85  Switching Cycles 8000  Frequency (Hz) 50/60  Energy Consumption (kWh/1000h) 4  Dimensions  Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Life Hours	15000
CRI (ra) 85  Switching Cycles 8000  Frequency (Hz) 50/60  Energy Consumption (kWh/1000h) 4  Dimensions  Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Beam Angle	300°
Switching Cycles 8000  Frequency (Hz) 50/60  Energy Consumption (kWh/1000h) 4  Dimensions  Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Energy Rating	Е
Frequency (Hz) 50/60  Energy Consumption (kWh/1000h) 4  Dimensions  Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	CRI (ra)	85
Energy Consumption (kWh/1000h)  Dimensions  Height (mm)  Diameter (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)	Switching Cycles	8000
Dimensions  Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Frequency (Hz)	50/60
Height (mm) 102  Diameter (mm) 60  Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Energy Consumption (kWh/1000h)	4
Packaging Information  Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Height (mm)	
Single Carton Height (mm) 125  Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Diameter (mm)	60
Single Carton Width (mm) 65  Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Packaging Information	
Single Carton Depth (mm) 65  Single Carton Weight (kg) 0.05  Individual Volume 0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Single Carton Height (mm)	125
Single Carton Weight (kg)  Individual Volume  0.00053  Inner Box Qty  10  Inner Box Height (mm)  140  Inner Box Width (mm)  340  Inner Box Depth (mm)  140  Inner Box Weight (kg)  0.65	Single Carton Width (mm)	65
Individual Volume  0.00053  Inner Box Qty 10  Inner Box Height (mm) 140  Inner Box Width (mm) 340  Inner Box Depth (mm) 140  Inner Box Weight (kg) 0.65	Single Carton Depth (mm)	65
Inner Box Qty 10 Inner Box Height (mm) 140 Inner Box Width (mm) 340 Inner Box Depth (mm) 140 Inner Box Weight (kg) 0.65	Single Carton Weight (kg)	0.05
Inner Box Height (mm) 140 Inner Box Width (mm) 340 Inner Box Depth (mm) 140 Inner Box Weight (kg) 0.65	Individual Volume	0.00053
Inner Box Width (mm)340Inner Box Depth (mm)140Inner Box Weight (kg)0.65	Inner Box Qty	10
Inner Box Depth (mm) 140 Inner Box Weight (kg) 0.65	Inner Box Height (mm)	140
Inner Box Weight (kg) 0.65	Inner Box Width (mm)	340
	Inner Box Depth (mm)	140
Outer Box Qty 100	Inner Box Weight (kg)	0.65
	Outer Box Qty	100
Outer Box Height (mm) 675	Outer Box Height (mm)	675
Outer Box Width (mm) 335	Outer Box Width (mm)	335
	Outer Box Depth (mm)	260
Outer Box Depth (mm) 260	Outer Box Weight (kg)	6.92







# LED 4W Dimmable Satin Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588052878
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Cap	ES/E27
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	450
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information Single Carton Height (mm)	125
Single Carton Height (mm)	125 65
Single Carton Height (mm) Single Carton Width (mm)	65
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	
Single Carton Height (mm) Single Carton Width (mm)	65 65
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)	65 65 0.05
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume	65 65 0.05 0.00053
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty	65 65 0.05 0.00053 10
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)	65 65 0.05 0.00053 10 140
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)	65 65 0.05 0.00053 10 140 340
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)	65 65 0.05 0.00053 10 140 340 140
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)	65 65 0.05 0.00053 10 140 340 140 0.65
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty	65 65 0.05 0.00053 10 140 340 140 0.65 100
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty  Outer Box Height (mm)	65 65 0.05 0.00053 10 140 340 140 0.65 100 675







# LED 6W Dimmable Satin Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588052892
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	6
Сар	ES/E27
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	Е
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information	60
	125
Packaging Information	
Packaging Information Single Carton Height (mm)	125
Packaging Information Single Carton Height (mm) Single Carton Width (mm)	125 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	125 65 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	125 65 65 0.05
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume	125 65 65 0.05 0.00053
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	125 65 65 0.05 0.00053
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm)	125 65 65 0.05 0.00053 10
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	125 65 65 0.05 0.00053 10 140 340 140 0.65 100 675







# LED 4W Dimmable Clear Filament GLS - BC - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588053004
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Cap	BC/B22
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information	60
	125
Packaging Information	
Packaging Information Single Carton Height (mm)	125
Packaging Information Single Carton Height (mm) Single Carton Width (mm)	125 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	125 65 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	125 65 65 0.05
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume	125 65 65 0.05 0.00053
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	125 65 65 0.05 0.00053
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm)	125 65 65 0.05 0.00053 10 140
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	125 65 65 0.05 0.00053 10 140 340 140 0.65 100 675







# LED 6W Dimmable Clear Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588053042
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	6
Сар	ES/E27
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
Height (mm) Diameter (mm)	102 60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







# LED 4W Dimmable Clear Filament GLS - BC - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588600499
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Cap	BC/B22
Colour Temp (K)	4000
Dimmable?	Yes
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions	
Height (mm)	102
Diameter (mm)	60
Diameter (IIIII)	
Packaging Information	
Packaging Information Single Carton Height (mm)	125
	125 65
Single Carton Height (mm)	
Single Carton Height (mm) Single Carton Width (mm)	65
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	65 65
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)	65 65 0.05
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume	65 65 0.05 0.00053
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty	65 65 0.05 0.00053
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)	65 65 0.05 0.00053 10 140
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)	65 65 0.05 0.00053 10 140 340
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)	65 65 0.05 0.00053 10 140 340
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)	65 65 0.05 0.00053 10 140 340 140 0.65
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty	65 65 0.05 0.00053 10 140 340 140 0.65 100
Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty  Outer Box Height (mm)	65 65 0.05 0.00053 10 140 340 140 0.65 100 675







# LED 4W Dimmable Clear Filament GLS - ES - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588600505
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Cap	ES/E27
Colour Temp (K)	4000
Dimmable?	Yes
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information	
	405
Single Carton Height (mm)	125
Single Carton Height (mm) Single Carton Width (mm)	65
Single Carton Width (mm)	65
Single Carton Width (mm) Single Carton Depth (mm)	65 65
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	65 65 0.05
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume	65 65 0.05 0.00053
Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	65 65 0.05 0.00053 10
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)	65 65 0.05 0.00053 10 140
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)	65 65 0.05 0.00053 10 140 340
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)	65 65 0.05 0.00053 10 140 340 140
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)	65 65 0.05 0.00053 10 140 340 140 0.65
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Width (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty	65 65 0.05 0.00053 10 140 340 140 0.65 100
Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (kg)  Individual Volume  Inner Box Qty  Inner Box Height (mm)  Inner Box Depth (mm)  Inner Box Weight (kg)  Outer Box Qty  Outer Box Height (mm)	65 65 0.05 0.00053 10 140 340 140 0.65 100 675







# LED 6W Clear Dimmable Filament GLS - BC - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588600512
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	6
Сар	BC/B22
Colour Temp (K)	4000
Dimmable?	Yes
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
Dimensions	
Height (mm)	102
Diameter (mm)	60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







# LED 12W Dimmable Clear Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588601816
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	12
Сар	ES/E27
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	1550
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	67mA
Energy Consumption (kWh/1000h)	12
Dimensions	
Height (mm)	70
Diameter (mm)	128
Packaging Information	
Single Carton Height (mm)	145
Single Carton Width (mm)	75
Single Carton Depth (mm)	75
Single Carton Weight (kg)	0.06
Individual Volume	0.00082
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	50
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







# LED 12W Dimmable Clear Filament GLS - BC - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

**Product Code** 

### **Technical Specification**

Reference	
Guarantee	3 Years
EAN	5013588601830
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	12
Сар	BC/B22
Colour Temp (K)	2700
Dimmable?	Yes
Lumens (lm)	1550
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	67mA
Energy Consumption (kWh/1000h)	12
Dimensions	
Height (mm)	70
Diameter (mm)	128
Packaging Information	
Single Carton Height (mm)	145
Single Carton Width (mm)	75
Single Carton Depth (mm)	75
Single Carton Weight (kg)	0.06
Individual Volume	0.00082
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	50
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92

