



LED 6W Clear Filament GLS - BC - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Product Code

Technical Specification

Reference	

Guarantee	3 Years
EAN	5013588050188
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	6
Cap	BC/B22
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	35mA
Energy Consumption (kWh/1000h)	6
Di	
Dimensions	
Height (mm)	102
Diameter (mm)	60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







LED 4W Satin Filament GLS - BC - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Technical Specification

Product Code	05121

Reference

Guarantee	3 Years
EAN	5013588051215
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Сар	BC/B22
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	22mA
Energy Consumption (kWh/1000h)	4
Dimensions	
	402
Height (mm)	102
Diameter (mm)	60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







LED 4W Satin Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Technical Specification

Product Code	05122

Reference

Guarantee	3 Years
EAN	5013588051222
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Сар	ES/E27
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	22mA
Energy Consumption (kWh/1000h)	4
Dimensions	
Height (mm)	102
Diameter (mm)	60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92







LED 4W Clear Filament GLS - BC - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Product Code

Technical Specification

Reference		
Guarantee	3 Years	

Guarantee	3 Years
EAN	5013588600451
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	4
Cap	BC/B22
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information	
Packaging Information Single Carton Height (mm)	125
Packaging Information Single Carton Height (mm) Single Carton Width (mm)	125 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	125
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	125 65 65 0.05
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	125 65 65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	125 65 65 0.05
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm)	125 65 65 0.05 0.00053 10
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	125 65 65 0.05 0.00053 10 140 340
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	125 65 65 0.05 0.00053 10 140 340 140 0.65
Packaging Information Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	125 65 65 0.05 0.00053 10 140 340 140 0.65 100







LED 4W Clear Filament GLS - ES - 4000K




The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Product Code

Technical Specification

Reference	
Guarantee	3 Years
EAN	5013588600468









Volts (V)	240
Watts (W)	4
Сар	ES/E27
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	470
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	4
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	100
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260







LED 6W Clear Filament GLS - BC - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Product Code

Technical Specification

Reference	
Guarantee	3 Years
	5047500600475

Guarantee	3 Years
EAN	5013588600475
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628
Country of Origin	CN







Volts (V)	240
Watts (W)	6
Сар	BC/B22
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
Dimensions Height (mm)	102
Diameter (mm)	60
Packaging Information	405
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Depth (mm)	65
Single Carton Weight (kg)	0.05
Individual Volume	0.00053
Inner Box Qty	10
Inner Box Height (mm)	
	140
Inner Box Width (mm)	140 340
Inner Box Width (mm) Inner Box Depth (mm)	140 340 140
Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	140 340 140 0.65
Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	140 340 140 0.65 100
Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	140 340 140 0.65 100 675
Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm) Outer Box Width (mm)	140 340 140 0.65 100 675 335
Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	140 340 140 0.65 100 675







LED 6W Clear Filament GLS - ES - 4000K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Product Code

Technical Specification

Reference	
Guarantee	3 Years

Guarantee	3 fears
EAN	5013588600482
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	6
Cap	ES/E27
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	810
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
Dimensions Height (mm) Diameter (mm)	102 60
Packaging Information	
Single Carton Height (mm)	125
Single Carton Width (mm)	65
Single Carton Width (mm) Single Carton Depth (mm)	65 65
Single Carton Depth (mm)	65
Single Carton Depth (mm) Single Carton Weight (kg)	65 0.05
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume	65 0.05 0.00053
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	65 0.05 0.00053 10
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm)	65 0.05 0.00053 10 140
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm)	65 0.05 0.00053 10 140 340
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm)	65 0.05 0.00053 10 140 340 140
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg)	65 0.05 0.00053 10 140 340 140 0.65
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty	65 0.05 0.00053 10 140 340 140 0.65 100
Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Inner Box Height (mm) Inner Box Width (mm) Inner Box Depth (mm) Inner Box Weight (kg) Outer Box Qty Outer Box Height (mm)	65 0.05 0.00053 10 140 340 140 0.65 100 675







LED 12W Clear Filament GLS - ES - 2700K



The LED Filament Range combines LED technology with the elegance of Incandescent Lamps. Creating a welcoming atmosphere with a retro feel, our LED Filament Range offers smooth dimming on rotary and digital dimming systems. The Filament GLS is an all rounder for decorative applications due to the wide range of wattages we offer.

- LED Technology with the elegance of Incandescent Lamps.
- Creates a welcoming atmosphere with retro feel.
- Argon gas filled to improve life.
- Smooth dimming on rotary and digital dimming systems.
- Full glass envelope.

Technical Specification

Product Code	60180

Reference

Guarantee	3 Years
EAN	5013588601809
Commodity Code	8539520000
Country of Origin	CN
UNSPSC Code	39101628







Volts (V)	240
Watts (W)	12
Cap	ES/E27
Colour Temp (K)	2700
Dimmable?	No
Lumens (lm)	1550
Life Hours	15000
Beam Angle	300°
Energy Rating	E
CRI (ra)	85
Switching Cycles	8000
Frequency (Hz)	50/60
LED Drive Current	103mA
Energy Consumption (kWh/1000h)	12
Dimensions	
Height (mm)	70
Diameter (mm)	128
Diameter (IIIII)	120
Packaging Information	
Single Carton Height (mm)	145
Single Carton Width (mm)	75
Single Carton Depth (mm)	75
Single Carton Weight (kg)	0.06
Individual Volume	0.00082
Inner Box Qty	10
Inner Box Height (mm)	140
Inner Box Width (mm)	340
Inner Box Depth (mm)	140
Inner Box Weight (kg)	0.65
Outer Box Qty	50
Outer Box Height (mm)	675
Outer Box Width (mm)	335
Outer Box Depth (mm)	260
Outer Box Weight (kg)	6.92

