



RoadFlair Pro

BRP593 LED263/NW 150W DW2 PSA GC

RoadFlair Pro, 26300 lm, 150 W, 740 neutral white, depends on driver (1-10V, DALI...), Safety class I

Municipalities value energy saving more than ever, as energy price hikes put increasing pressure on the budgets. Street lighting consumes substantial energy, so large-scale upgrades to energy-efficient LED streetlights are fundamental to cities' cost-saving efforts. RoadFlair Pro has been upgraded to minimize costs while maximizing efficacy, safety, and functionality. And the best part - RoadFlair Pro offers a streamlined design, so it maintains an attractive aesthetic on city streets. These streetlights not only look good, they also offer excellent performance. Future-proof technology combines with high efficacy (160 lm/W and 200 lm/W), innovative design, and smart connectivity in a light that makes your street look brighter and better

Product data

General Information		Operating and Electrical	
Driver included	Yes	Input Voltage	220-240 V
Service tag	Yes	Line Frequency	50 or 60 Hz
Value ladder	Specification	Power Consumption	150 W
		Power Factor (Fraction)	0.95
		Connection	Connection unit 5-pole
		Cable	-
		Protection class IEC	Safety class I
Light Technical		Controls and Dimming	
Luminous Flux	26,300 lm	Dimmable	1-10V
Correlated Color Temperature (Nom)	4000 K	Control interface	depends on driver (1-10V, DALI...)
Luminous Efficacy (rated) (Nom)	176 lm/W		
Color rendering index (CRI)	70		
Light source color	740 neutral white		
Effective projected area	0.11 m ²		

RoadFlair Pro

Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Housing Color	RAL7040
Overall length	578.4 mm
Overall width	189.5 mm
Overall height	96 mm
Dimensions (Height x Width x Depth)	96 x 190 x 578 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Clear dome
Net Weight (Piece)	3.750 kg

Approval and Application

Flammability mark	-
CE mark	Yes

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Power consumption tolerance	+/-10%

Product Data

Order product name	BRP593 LED263/NW 150W DW2 PSA GC
Full product name	BRP593 LED263/NW 150W DW2 PSA GC
Order code	911401649109
Material Nr. (12NC)	911401649109
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

