PHILIPS Lighting



TrueForce LED Industrial and Retail (Highbay – HPI/SON/HPL)

TForce ESS LED HB MV 4.5Klm 45W 865 E27

Philips TrueForce LED Industrial and Retail lamps give you a quick and easy payback solution to replace HID lamps in Highbay application. The solution gives you the LED benefits of energy-efficiency and long-lifetime, plus they come for a low initial investment. With unique lamp design and compatibility, you can directly retrofit HID lamps with TrueForce LED lamps without changing the fixtures or gear. Multiple beam angle options and high colour rendering index enhance the lighting distribution while creating a comfortable, safe and high productivity environment.

Warnings and Safety

• EM version requires an EM ballast to operate. Please refer to the installation guide or consult a Philips Lighting representative.

Product data


neral Information		Luminous Efficacy (rated) (Nom)	100 lm/
ap-Base	E27	Color Designation	Cool Daylig
Nominal lifetime	15,000 hour(s)	Correlated Color Temperature (Nom)	6500 K
Switching Cycle	50,000	Color Consistency	<6
Lighting Technology	LED	Color rendering index (CRI)	80
		LLMF At End Of Nominal Lifetime (Nom)	70 %
Light Technical			
Color Code	865 [CCT of 6500K]	Operating and Electrical	
Beam Angle (Nom)	180 degree(s)	Line Frequency	50 to 60 Hz
Luminous Flux	4.500 lm	Input Frequency	50 to 60 Hz

TrueForce LED Industrial and Retail (Highbay - HPI/SON/HPL)

Power Consumption	45 W	
Lamp Current (Nom)	356 mA	
Starting Time (Nom)	0.5 s	
Warm-up time to 60% light	0.5 s	
Power Factor (Fraction)	0.5	
Voltage (Nom)	220-240 V	
Temperature		
Ambient temperature range	-20 °C to 45 °C	
T-Case Maximum (Nom)	77 °C	
Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Bulb Finish	Frosted	
Bulb Shape	T120	

Yes
TForce ESS LED HB MV 4.5Klm 45W 865 E27
TForce ESS LED HB MV 4.5Klm 45W 865 E27
872016919021400
929003632108
929003632108
1
0.142 kg
8720169190214
6
8720169190221

Dimensional drawing



TForce ESS LED HB MV 4.5Klm 45W 865 E27	121 mm	199 mm

D

с

Spectral Power Distribution Colour - TForce ESS LED HB MV 4.5Klm 45W 865 E27


Photometric data

		1 x 655 HPI 45W 9299316331	
		1 x 4300 im	
Pair inersity degree.	Duantice nationalise diagram	LGR diagram	
	A second		
	Unitation ferror rable	Laminance Table	
Real Property of Contract of C			

General uniform lighting - TForce ESS LED HB MV 4.5Klm 45W 865 E27

Product


TrueForce LED Industrial and Retail (Highbay - HPI/SON/HPL)



Photometric data

Light Distribution Diagram - TForce ESS LED HB MV 4.5Klm 45W 865 E27

Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram - TForce ESS LED HB MV 4.5Klm 45W 865 E27



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2024, August 9 - data subject to change