



MASTER LEDtube T8

MAS LEDtube 1200mm HO 13W840 T8

MASTER, LEDtube, T8, EM/Mains, Single-end, 1200 mm, 220-240 V, 13 W, 36W TL-D, 4000 K, 2100 lm, 60000 hour(s)

MASTER, LEDtube, T8, EM/Mains, Single-end, 1200 mm, 220-240 V, 13 W, LED alternative to 36W TL-D, 4000 K, 2100 lm, 60000 hour(s), 161 lm/W, G13, Beam angle 190 degree(s), Plastic, RGO

Warnings and Safety

- NOTE: The overall energy efficiency and light distribution of any installation that uses these lamps will be determined by the design of the installation.

Product data

General Information	
Cap-Base	G13
Nominal lifetime	60,000 hour(s)
Switching Cycle	200,000
Lighting Technology	LEDtube
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	190 degree(s)
Luminous Flux	2,100 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	161 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Photobiological safety according to EN 62471 RGO	
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power Consumption	13 W
Lamp Current (Max)	63 mA
Lamp Current (Min)	58 mA
Wattage Equivalent	36 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	36W TL-D
Ballast Compatibility	EM/Mains

MASTER LEDtube T8

Temperature	
T-Case Maximum (Nom)	50 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	1,200 mm
Bulb Shape	T8
Net Weight (Piece)	0.180 kg
Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance KEMA Keur certificate
EU RoHS compliant	Yes



Ambient temperature range	-20 to +45 °C
Application Conditions	
Wireless Technology	Not applicable
Product Data	
Order product name	MAS LEDtube 1200mm HO 13W840 T8
Full product name	MAS LEDtube 1200mm HO 13W840 T8
Full product code	872016931607200
Order code	929003806108
Material Nr. (12NC)	929003806108
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169316072
Numerator - Packs per outer box	20
EAN/UPC - Case	8720169316089

Dimensional drawing



Product	D1	D2	A1	A2	A3
MAS LEDtube 1200mm HO 13W840 T8	25.8 mm	28 mm	1,198.2 mm	1,205.3 mm	1,212.4 mm

Photometric data




General uniform lighting - MAS LEDtube 1200mm HO 13W840 T8

Spectral Power Distribution Colour - MAS LEDtube 1200mm HO 13W840 T8


MASTER LEDtube T8

Photometric data




Light Distribution Diagram - MAS LEDtube 1200mm HO 13W840 T8


Lifetime




LEDtube 60K 5070 LifetimeVsTc-LED



Lumen Maintenance Diagram - MAS LEDtube 1200mm HO 13W840 T8




Life Expectancy Diagram



LEDtube 60K 5070 FailureRate-LED

MASTER LEDtube T8

Lifetime



Lumen Maintenance Diagram - MAS LEDtube 1200mm HO 13W840 T8

