

LED Torch IP65



- High luminous Cree LED
- Operating time over 4 hours (full power)
- Recharge time less than 3 hours
- Zones 21 and 22, temp class 4
- LED-bar indicator for battery capacity
- Also available with emergency lighting function (EM)

Model	ML-808 ATEX, ML-808 EM ATEX
<i>Product description</i>	ML-808 ATEX: Rechargeable safety hand lamp ML-808 ATEX EM: Rechargeable emergency safety lamp
<i>Certification</i>	ATEX: VTT 13 ATEX 024 Issue 1 II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135 °C Db
<i>Area of operation</i>	Gas: zones 1 and 2 Dust: zones 21 and 22
<i>Temp. classification</i>	Gas: T4 Dust: 135 °C
<i>Operating temperature</i>	-20°C ... +40°C
<i>Light source</i>	1 high luminous Cree LED Lifetime: 50 000hrs
<i>Light output</i>	Full power: Over 100 lm Low power: 25 lm
<i>Operating time</i>	Full power: 4 hrs 30 min Low power: 15 hrs
<i>Beam type</i>	Spot
<i>Lens</i>	Tempered glass 41.5 x 3.2 mm
<i>Enclosure</i>	Dissipative (antistatic) polypropylene + aluminium
<i>Ingression protection</i>	IP 65
<i>Power source</i>	6V rechargeable NiMH battery
<i>Weight with battery</i>	0.40 kg
<i>Dimensions</i>	120 mm (H) x 63 mm (W) x 54 mm (L)
<i>Charging time</i>	2 hrs 30 min
<i>Other features</i>	Deep discharge prevention Battery capacity indicator Low battery warning Wrist strap
<i>Chargers</i>	MICA MLC Single fast charger (12..24VDC)