

N150MF MAINTENANCE-FREE TRUCK BATTERY

This product has excellent characteristics of large current discharge, advance lead calcium alloy and special diachylon method, anti-acid mist filter plate, anti-shake, prevent coldness, low discharge, less water losing, well cold starting capability, etc.

电池规格 SPECIFICATIONS

标称电压 Nominal Voltage	12V
额定容量 Rated Capacity	150Ah @20hr to 10.5V @25°C
储备容量 Reserve Capacity	292min @RC to 10.5V @25°C
电池重量 Weight	38.22kg ± 3%
尺寸 Dimensions	506×221×210×233(mm)
卡表CCA Tester CCA	1100
使用温度 Usage Temperature	Discharge: -40°C ~ 60°C
	Charge: -40°C ~ 60°C
	Storage: -40°C ~ 60°C
最佳使用温度 The Best Usage Temperature	10°C ~ 30°C
恒流充电电流 Constant Charging Current	15.0A
恒压充电电压 Constant Charging Voltage	13.8V
最大充电电流 Max.Charge Current	37.5A
最大放电电流 Max.Discharge Current	1100 A
端子 Terminal	Tapered terminals/Flat head terminals
槽盖材料 Battery Case material	PP
执行标准 Execution Standard	GB/T 5008.1-2013

