

Product datasheet

Specifications



Switched socket, ESM, 13A, 1 gang

ESMT15

Main

Range	ESM
Product or component type	Switched socket
Assembly Type	Complete product
Device application	Energy management
Colour tint	Grey
Control type	Control
Technology type	Electromechanical
Protection	Shuttered
Main colour tint	Grey

Complementary

Control type	Rocker
Number of gangs	1 gang
Number Of Outlets	1
Actuator	Rocker
Mounting Type	By screw
Installation Type	Surface
Material	PC Steel
Surface finish	Powder coated
[Ue] rated operational voltage	250 V AC
Network frequency	50/60 Hz
[In] rated current	13 A
Connections - terminals	2 x 4 mm ² screw terminal for rigid or flexible cable
Depth	49 mm
Height	86 mm
Width	86 mm
Mounting Centers	60.3 mm
Net Weight	0.2828 kg
surface treatment	Painted
Wire stripping length	12 mm
Number of power socket outlets	1 x 2P + E

Number Of Switches	1
--------------------	---

Environment

IP degree of protection	IP20
-------------------------	------

IK degree of protection	IK08
-------------------------	------

Ambient air temperature for storage	-20...60 °C
-------------------------------------	-------------

Standards	BS 1363 MS 589 SS 145
-----------	-----------------------------

Relative humidity	0...95 %
-------------------	----------

Ambient air temperature for operation	-5...45 °C
---------------------------------------	------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	9 cm
------------------	------

Package 1 Width	5.4 cm
-----------------	--------

Package 1 Length	9 cm
------------------	------

Package 1 Weight	300.8 g
------------------	---------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	9.7 cm
------------------	--------

Package 2 Width	19 cm
-----------------	-------

Package 2 Length	28.2 cm
------------------	---------

Package 2 Weight	3.18 kg
------------------	---------

Unit Type of Package 3	CAR
------------------------	-----

Number of Units in Package 3	40
------------------------------	----

Package 3 Height	21 cm
------------------	-------

Package 3 Width	29.5 cm
-----------------	---------

Package 3 Length	39.5 cm
------------------	---------

Package 3 Weight	13.4 kg
------------------	---------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	15 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	11 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	No
Silicone-free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	84
End of life manual availability	No need of specific recycling operations

Image of product / Alternate images

Alternative







