



EL-LED2 LED BULKHEAD



NON-MAINTAINED EMERGENCY BULKHEAD SUITABLE FOR WET AND DRY AREAS

- Low Heat generation, ensures long and reliable service life.
- Low battery voltage cut-off with latch function, to eliminate battery over discharge.
- Charge LED indicator and test switch
- Weatherproof design suitable for wet and dry applications.
- Optimal for anti-panic (open area) and escape route lighting applications
- High Quality, Long Life LED module.
- Spring bracket available for surface or semi recess installation
- Recess plate available for fully recess installation (IP40)

TECHNICAL SPECIFICATION

MODEL NO:	EL-LED2
Mode of Operation:	Non-Maintained
Lamp:	6W White LED
Rated Duration:	3 Hours
Mains Supply:	220-240 Volts, 50-60Hz
Power Consumption:	<0.5W after fully charged
Battery:	High Temperature Lithium LiFePO4
Charger:	Constant current / Constant voltage, short circuit protected
Charge Monitor:	LED
Test Facility:	Momentary Test Switch
Safety Features:	Low battery voltage cut off to prevent over discharge
Fitting Construction:	Injection moulded with fire retardant (UL94), high impact PC/ABS material
Ingress Protection:	IP65 for surface or semi recess IP40 for fully recess installation
Weight:	Approx. 0.6kg
Dimensions:	121mm (H) x 278mm (W) x 41mm (D)
Standards / Compliance:	SS IEC 60598-2-22, SS 563

ORDERING GUIDE

EL-LED2NM-Li

***Note : Technical Specification subject to change without prior notice