



Two types of dimensions available for Recess Plate:



# EX-SB-M SLIM BLADE EXIT



## AESTHETIC, FUNCTIONAL AND COMPACT DESIGN

- Designed for fast installation and easy maintenance.
- Extra low power consumption
- High Quality, Long Life SMD LED module
- Numerous installations option available
- Low battery voltage cut-off with latch function, to eliminate battery over discharge
- Durable fire retardant construction (UL 94)
- Lightweight ergonomics design boost productivity of installers

## TECHNICAL SPECIFICATION

<b>MODEL NO:</b>	<b>EX-SB-M</b>
Mode of Operation:	Maintained
Lamp:	White LED module with life-span > 100,000 hours
Rated Duration:	3 Hours
Mains Supply:	220-240 Volts, 50-60Hz
Power Consumption:	2.5W (Total standby power inclusive of LED converter)
Battery:	High Temperature Lithium LiFePO4 / High Temperature Nickel Cadmium
Charger:	Regulated variable rate
Charge Monitor:	LED
Test Facility:	Micro switch
Mounting:	Surface wall / Suspended / Surface ceiling / Recessed ceiling
Safety Features:	Low battery voltage cut off to prevent over discharge
Diffuser:	Acrylic plate (fire retardant)
Fitting Construction:	Injection moulded with fire retardant (UL94), high impact material
Weight:	Approx. 0.6kg
Dimensions:	223mm (H) x 314mm (W) x 37mm (D)
Standards / Compliance:	SS IEC 60598-2-22, SS 563

ORDERING GUIDE						ACCESSORY: RECESS MOUNT KIT
	Single Sided	Double Sided		Single Sided	Double Sided	
	EX-SB-M-S	EX-SB-M-D		EX-SB-M-S-RM	EX-SB-M-D-RM	<b>ORDERING GUIDE:</b>
	EX-SB-M-SR	EX-SB-M-DR		EX-SB-M-SR-RM	EX-SB-M-DR-RM	EX-SB-RC-ASSY 350 x 80MM
	EX-SB-M-SL	EX-SB-M-DL		EX-SB-M-SL-RM	EX-SB-M-DL-RM	EX-SB-RC-ASSY 448 x 90MM

\*\*\*Note : Technical Specification subject to change without prior notice