

SPECIFICATION SHEET

Solar Flood Light

Model

JD6001 100W

JD6001 200W

JD6001 300W

JD6001 400W



Life Span 30,000 Hours



Ingress Protection



High Efficient And Quality SMD LED Chips




Monocrystalline Solar Panel

	Wattage	100W	200W	300W	400W
Lamp Body	Light Source	SMD2835			
	Lumen	Max. 900lm	Max. 1800lm	Max. 2600lm	Max. 3500lm
	Casing Material	ABS + Glass			
	Battery	Capacity	3.2V 5,000mAH	3.2V 10,000mAH	3.2V 15,000mAH
	Material	LifePO4 Battery			
Solar Panel	Power	5V/10W	5V/25W	5V/30W	5V/40W
	Material	Monocrystalline			
Correlated Color Temp. (CCT)		3000K / 6500K			
Color Rendering Index (CRI)		>80			
Beam Angel		90°			
Index Protection (IP)		IP65			
Operating Temperature		-20°C~+50°C			
Carton		10	10	5	4

Measurement (mm)


Wattage	A	B	C	D	E	F
100W	170	200	35.4	200	210	17
200W	200	235	35.4	205	300	17
300W	230	265	37.4	235	390	17
400W	260	332	49.4	375	390	17



FRONT VIEW



SIDE VIEW



SOLAR PANEL