



TEL 33 SELF-CONTAINED EMERGENCY LUMINAIRES (IP20 or 65)



IP20

Dimension : 198L x 56W x 240H

IP65



Dimension : 198L x 82W x 235H

SPECIFICATION

Model	: TEL33 (IP20 or IP65)
System Mode	: Non Maintained Mode
Emergency Duration	: 2-3 hours
Lamp	: 2x High Output white LED.
Battery	: 4.8V 2.5AH High temperature nickel cadmium battery
Recharge Period	: 16 - 24 hours: Low Voltage cut off to prevent from overdischarging:
Battery Protection Monitoring	Green LED. "ON" indicates charging with pushtest switch to simulate power failure
Input Voltage	: 220-240V 50-60Hz
Housing Dimension	: Epoxy White Painted Housing (IP20) : Injection molded fire retardant ABS housing (IP65) : 195(L)x235(H)x82(D) mm for IP20/198(L)x240(H)x86(D) for IP65
Weight	: 2.45kg
Mounting	: Surface mounted
Warranty	: 1 Year
Compliance	: SS563-1:2010, SS563-2:2010/A1:2013, SS IEC60598-2-22:2016
Power Consumption	: 2x3.0 Watt
IP Rating	: IP 20 & IP 65

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.

