

TH50NM-WP WEATHERPROOF TWIN-SPOT LED

OUR WEATHERPROOF TWIN-SPOT IS
WELL PREPARED IN HARSH
ENVIRONMENTAL CONDITIONS.



TECHNICAL SPECIFICATIONS



MODEL NO:	TH50NM-WP
Mode of Operation:	Non-Maintained
Lamp:	2 x 10W Power LED Module
Rated Duration:	2 Hours / 3 Hours
Mains Supply:	220-240 Volts, 50-60Hz
Power Consumption:	< 3W
Battery:	High Temperature Lithium LiFePO4
Charger:	Constant Current / Constant Voltage, Short Circuit protected
Charge Monitor:	LED
Test Facility:	Momentary test switch
Safety Features:	Low battery voltage cut off to prevent over discharge
Fitting Construction:	Injection moulded with fire retardant (UL94), high impact PC material
Weight:	Approx. 1.6 Kg
Dimensions:	230mm (H) x 240mm (W) x 85mm (D)
Standards / Compliance:	SS IEC 60598-2-22, SS 563

Ordering Guide:

Ordering Code

TH50NM-WP

- Low heat generation, ensures long and reliable service life.
- Low battery voltage cut-off with latch function, to eliminate battery over discharge.
- Charge LED indicator and test switch.
- Weatherproof IP65 design suitable for indoor and outdoor applications.
- Adjustable lens for optimum matching to light requirements.



CLASS II



Type and batch tested with
PSB PLS-LISTED LABEL

IP65

***Note: Technical Specification subject to change without prior notice