

## **RIEGEL MARINE BATTERY SPECIFICATION**

| S/NO | TYPE    | CCA  | 20HR<br>A.H. | OVERALL DIMENSION |     |     | LAYOUT | TERMINAL | DRY WEIGHT<br>KGS |
|------|---------|------|--------------|-------------------|-----|-----|--------|----------|-------------------|
|      |         |      |              | L                 | W   | H   |        |          |                   |
| 0    | 12N32   | 250  | 32           | 165               | 126 | 165 | 1      | 1        | 9.0               |
| 1    | 53522   | 300  | 35           | 187               | 125 | 200 | 1      | 1        | 9.5               |
| 2    | NS40    | 350  | 36           | 185               | 125 | 200 | 1      | 3        | 9.8               |
| 3    | 39B19R  | 400  | 35           | 180               | 120 | 200 | 1      | 1        | 10.5              |
| 4    | NS60S   | 400  | 60           | 230               | 130 | 220 | 1      | 1        | 11.5              |
| 5    | 55D23L  | 530  | 60           | 225               | 165 | 190 | 1      | 1        | 12.8              |
| 6    | 80D26L  | 650  | 70           | 250               | 170 | 190 | 1      | 1        | 14.0              |
| 9    | 105D31R | 750  | 72           | 300               | 170 | 200 | 1      | 1        | 17.9              |
| 10   | N100    | 730  | 100          | 410               | 170 | 225 | 1      | 1        | 20.2              |
| 11   | NS120   | 900  | 120          | 400               | 170 | 220 | 1      | 1        | 26.3              |
| 12   | N120    | 820  | 120          | 500               | 180 | 225 | 1      | 1        | 32.2              |
| 13   | N150    | 980  | 150          | 500               | 220 | 225 | 1      | 1        | 38.8              |
| 14   | NS150   | 1000 | 140          | 500               | 180 | 210 | 1      | 1        | 35.8              |
| 15   | 210H52R | 1000 | 200          | 500               | 270 | 210 | 1      | 1        | 32.0              |
| 16   | N200    | 1200 | 176          | 520               | 270 | 210 | 1      | 1        | 45.5              |
| 17   | N225    | 1250 | 225          | 520               | 285 | 250 | 1      | 1        | 55.0              |

### **12 VOLT STARTER MF TYPE with 20 HR Rating**

|    |           |      |     |     |     |     |   |   |      |
|----|-----------|------|-----|-----|-----|-----|---|---|------|
| 18 | DIN45L    | 420  | 45  | 209 | 170 | 175 | 0 | 1 | 9.0  |
| 19 | DIN50L    | 500  | 50  | 210 | 170 | 175 | 0 | 1 | 9.6  |
| 20 | DIN60L    | 520  | 54  | 240 | 170 | 175 | 0 | 1 | 12.5 |
| 21 | DIN74L    | 680  | 74  | 277 | 170 | 190 | 1 | 1 | 14.0 |
| 22 | DIN80L    | 800  | 60  | 310 | 165 | 175 | 0 | 1 | 15.5 |
| 23 | 60044     | 780  | 100 | 350 | 170 | 190 | 1 | 1 | 23.0 |
| 24 | DIN180L   | 1100 | 180 | 480 | 220 | 195 | 1 | 1 | 39.0 |
| 25 | DIN200L   | 1200 | 200 | 490 | 230 | 200 | 1 | 1 | 42.9 |
| 26 | 6CQ-90    | 680  | 90  | 300 | 165 | 200 | 1 | 1 | 14.2 |
| 27 | 6QW-150   | 1000 | 150 | 500 | 225 | 210 | 1 | 1 | 38.0 |
| 28 | M24       | 700  | 60  | 260 | 165 | 200 | 1 | 1 | 15.0 |
| 29 | M27       | 780  | 90  | 310 | 170 | 200 | 0 | 1 | 17.0 |
| 30 | M31       | 850  | 100 | 329 | 170 | 210 | 0 | 1 | 20.3 |
| 31 | ESH200-12 | 1280 | 200 | 495 | 290 | 210 | 0 | 3 | 48.0 |
| 32 | ESH300-12 | 1380 | 300 | 520 | 295 | 230 | 0 | 3 | 54.5 |