

Random Orbit Sander LXT®

DBO180Z

18V • 125 mm

Powerful sander with efficient dust removal

A handy battery-powered random orbit sander with a pad diameter of 125 mm. Efficient dust removal and cordless operation for added comfort. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	14000 - 22000 min ⁻¹
Orbits per Minute	7000 - 11000 min ⁻¹
Sanding pad diameter	123 mm
Sanding Disc Diameter	125 mm
Sanding Orbit Diameter	2,8 mm
Sound Pressure Level (L _{pA})	77 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,4 - 1,7 kg
Product Dimensions (L x W x H):	175 x 123 x 153 mm
Vibration Level, Sanding Metal Plate	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Sanding Metal Plate	1,5 m/s ²

User benefits

- The rubber coating on the handle ensures a firm working grip
- 3-speed options (Low / Medium / High) allows the operator to match speed to application
- Efficient through-the-pad dust collection system for a cleaner work environment
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381658584

Link to product - www.makita.uk.com



Related products

Standard AC

166078-4
Dust Bag



Optional AC

135246-0
Dust Box + Paper dust bag 1 pc



196152-4
Felt pad 125 mm



450128-8
Battery cover, LXT®, 14,4 – 18V



743081-8
Rubber Pad 125 mm



794558-6
Sponge Pad 125 mm



794560-9
Wool pad 140 mm



821550-0
Makpac case (2)



837809-5
MakPac (2) Inlay



D-70867
Wool Pad 125 mm PO5000C



D-74631
Felt 125 mm



P-43533
Abrasive Disc 125 mm, 40G



P-43549
Abrasive Disc 125 mm, 60G



P-43555
Abrasive Disc 125 mm, 80G



P-43561
Abrasive Disc 125 mm, 100G



P-43577
Abrasive Disc 125 mm, 120G



P-43583
Abrasive Disc 125 mm, 180G



P-43599
Abrasive Disc 125 mm, 240G



Other

User manual

Parts drawing